

SLT-MT Series Turntable

Product Specifications



DESIGN HIGHLIGHTS

- 1 HP power unit 115V/1ph/60hz with 24 volt controls x 10' of hose
- · Power unit with UL approved electrical panel
- Push-button control NEMA 4X with 10' of cable
- Self lubricating bushings with hardened chrome pins for pivot points
- · Velocity fuses on all cylinders to prevent uncontrolled descent
- Maintenance Support Device
- Meets ANSI MH29.1 standard for industrial scissors lifts
- Double wire braided hydraulic hoses

AVAILABLE OPTIONS
☐ Non-standard turntable sizes*
☐ Pit mount options (consult factory)
☐ Special color
☐ Other
* Non-standard turntables must be equal to platform size. Add extra square footage for non-standard turntable and platform.

PROJECT INFORMATION	
JOB NAME	
ADDRESS	
GENERAL CONTRACTOR	
DISTRIBUTOR	
MODEL	_QUANTITY
VOLTAGE/PHASE	

DIMENSIONS						
MODEL	CAPACITY [lb]	PLATFORM SIZE [inches]	MAX TURNTABLE SIZE [inches]	RAISE LOWER TIME [sec]	SHIP WEIGHT [lb]	
SLT24-2MT	2,000	24 x 36	36 x 36	18	674	
SLT24-4MT	4,000	24 x 36	36 x 36	25	860	
SLT36-2MT	2,000	24 x 48	48 x 48	24	1,051	
SLT36-4MT	4,000	24 x 48	48 x 48	48	1,142	
SLT48-2MT	2,000	24 x 72	48 x 72	35	1,640	
SLT48-4MT	4,000	24 x 72	48 x 72	70	1,700	
SLT59-2MT	2,000	36 x 88	48 x 88	40	2,048	
SLT59-4MT	4,000	36 x 88	48 x 88	80	2,310	



Serco

1612 Hutton Drive, Suite 140 Carrollton, TX 75006 800.933.4834 www.sercodockproducts.com

4Front Engineered Solutions reserves the right to change specifications and designs without notice and without incurring obligations. 4Front Engineered Solutions products may be the subject of one or more U.S. and/or foreign, issued and/or pending, design and/or utility patents. Sero as word and logo are registered trademarks belonging to ASSA ABLOY Entrance Systems AB or other companies controlled by the same organization. All rights reserved.